



- Notes
- 46 1. wire material: Hera 649; 330±30 HV.
 - 47 2. spring material: CuBe2 HM R 930; 290-350 HV.
 - 48 3. notch - has to break after bending 90° forward and back.
 - 49 4. burr max.0,01mm.
 - 50 5. customer funktion and assembly tolerance 2,8±0,2mm
 - 6. contact force and funktion length measured in a product specific check appliance.
 - 51 7. welding strength >=20N for one brush.
 - 52 8. Fc measurement in check appliance # 87060439.
 - 9. delivery form in strips.

Allgemein
Toleranzen
DIN ISO 2768-f

t20714		Gespeichert am : 29. Jun 2010 07:54:56		Dateiname: OpenTool3_ezt_80377845	
Elektronik		10:1		CuBe2 / Hera 649	
Erstellt: 29.06.2010		Geprüft: 29.06.2010		Benennung: Multiwire wiper Open-Tool-3	
Zustimmend:		Zustimmend:		Zustimmend:	
Schutzvermerk nach DIN ISO 15016 beachten		Schutzvermerk nach DIN ISO 15016 beachten		Schutzvermerk nach DIN ISO 15016 beachten	
Bestellnummer: TZ009		Zeichnungsnummer: 80377845		Format: A2	
Blatt: 1		Blatt: 1		Blatt: 1	